

**Mobil™ ATF 134 FE**

Mobil Passenger Vehicle Lube, Italy

Automatic Transmission Fluid

Product Description

Mobil™ ATF 134 FE is an Automatic Transmission Fluid especially developed to further optimize gearbox efficiency of latest generation Mercedes-Benz 7-G Tronic Plus automatic transmissions.

Features and Benefits

Mobil ATF 134 is formulated with an advanced additive system in combination with a carefully selected composition of base oils providing excellent thermal stability and wear resistance as well as very good low temperature properties.

Applications

Mobil ATF 134 FE is designed for the Daimler automatic transmission type 7-G Tronic Plus. The below articles are introduced for all markets where the predecessor product (Mobil ATF 134) has been sold previously. Mobil ATF 134 FE is only miscible with other officially approved MB 236.15 ATF's and not backwards compatible with previous MB-ATF specifications.

Specifications and Approvals

Mobil ATF 134 FE has the following builder approvals	
MB-Approval 236.15	X

Typical Properties

Mobil ATF 134 FE	
Colour, DIN ISO 2549	Blue
Viscosity, DIN 51 562-1	
cSt @ 40°C	16
cSt @ 100°C	4,2
Viscosity at -40 °C, DIN 51398 mPas	3500
Pour Point, °C, DIN ISO 3016, min	-48
Flash Point, °C, DIN ISO 2592	186
Viscosity Index, DIN ISO 2909	176

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Delvac (and any other trademarks) are trademarks of Exxon Mobil Corporation, or one of its subsidiaries
02-2018

Esso Italiana s.r.l.

Via Castello della Magliana 25

00148, Roma, Italia

800.011723

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil



© Copyright 2003-2017 Exxon Mobil Corporation. All

Rights Reserved.