Mobil ATF D 21065 Page 1 of 2



# Mobil ATF D 21065

Mobil Passenger Vehicle Lube, Italy

Automatic Transmission Fluid

# **Product Description**

Mobil ATF D 21065 is an Automatic Transmission Fluid blended to a unique formulation using highly refined base oils and performance additives. This transmission fluid is approved as a factory fill for PSA.

## Features and Benefits

- Long transmission life.
- Outstanding friction durability for improved shift feel.
- Excellent cold flow properties.

# Specifications and Approvals

| Mobil ATF D 21065 has the following approval: |   |
|---|---|
| MB-Approval 235.71                            | Х |
| Approved TE-ML 04D/09/11B                     | Х |
| PSA S712102                                   | Х |

| According to ExxonMobil , Mobil ATF D 21065 is of the following quality level: |   |
|--|---|
| GM DEXRON II D   | X |

# **Typical Properties**

| Mobil ATF D 21065 |      |
|-------------------|------|
| Viscosity         |      |
| cSt @ 100°C       | 7.4  |
| cSt @ 40 °C       | 38.2 |
| Viscosity Index   | 164  |
| Flash Point, °C   | 208  |
| Density kg/m3     | 868  |

# Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

04-2016

Mobil ATF D 21065 Page 2 of 2

### Esso Italiana s.r.l.

Via Castello della Magliana 25 00148, Roma, Italia

### 800.011723

### http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

